



Samar

cat. B

100% polyester FR
Flame retardant - 50.000 Martindale



7052.01




7052.02



7052.04



7052.05



7052.07



7052.08




7052.09



7052.10




7052.11




7052.12




7052.13




7052.14




7052.16




7052.17




7052.19



7052.21



7052.22



7052.23




7052.24




7052.25



7052.26



7052.27



7052.29




7052.30



7052.33




7052.34



7052.36



7052.38



7052.39



7052.40



7052.41




7052.42



7052.43



7052.44




7052.45




7052.46




7052.47



7052.49



7052.50



7052.51

<div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> <div></div> </div>	Samar		Technical details	
	Composition	100% polyester FR		
	Weight	Gr./ml. 660		
	Abrasion test	Martindale - ISO 12947-2: 50.000 rubs		
	Lightfastness	ISO 105-B02: 6		
	Pilling	ISO 12945-2: 4/5		
	Fastness to rubbing	ISO 105-X12: Wet 4/5 Dry 4/5		
	Flame retardant	EN 1021/1-2 BS 5852, crib 5 NF P 92/503-507, M1 DIN 4102, B1 IMO 2010 FTP part 8 UNI 9175, classe 1		
	Environment	Oeko-Tex 100 certified		
laCividina		cat. B	2018	