














Lineal Suspended is a modular system solution for suspended installation. Lineal provides an efficient and uniform lighting experience, and is supplied with both upward and downward lighting. The range comes in the standard colours black and white. The opalprism front on the roll ensures seamless light without joints. SG also delivers customised solutions beyond the standard product range. With a lifespan of up to 100,000 hours, consistent and elegant lighting is ensured for many years.






For each continuous line, you need one or more straight lines and/or corners, a starter kit and a front foil. Lineal Suspended can be combined with Lineal Cubic Surface/Suspended, allowing for creative lighting designs.








## Product- and environment images


















Article	Protection	Control gear	Mounting/Connection	Dimensions
<b>840</b>				
 8246094607 <b>Lineal suspended 840 Black</b> <b>2360lm 3000K Ra&gt;80 DALI / Push Dim</b> <b>21W LED</b> 112 lm/W SDCM:3 L80/B10>100,000, L93/>50,000 Direct/Indirect 50/50%,	<b>Class I</b> <b>IP20</b> <b>IK08</b>	DALI / Push Dim	Suspended, Indoor 1x2m wire kit w/ceiling bracket 5-pole Winsta mini with 5x2,5mm2 through wiring	L841 x W42 x H70
 8246094610 <b>Lineal suspended 840 Black</b> <b>2480lm 4000K Ra&gt;80 DALI / Push Dim</b> <b>21W LED</b> 118 lm/W SDCM:3 L80/B10>100,000, L93/>50,000 Direct/Indirect 50/50%,	<b>Class I</b> <b>IP20</b> <b>IK08</b>	DALI / Push Dim	Suspended, Indoor 1x2m wire kit w/ceiling bracket 5-pole Winsta mini with 5x2,5mm2 through wiring	L841 x W42 x H70
 8246094665 <b>Lineal suspended 840 White</b> <b>2520lm 3000K Ra&gt;80 DALI / Push Dim</b> <b>21W LED</b> 120 lm/W SDCM:3 L80/B10>100,000, L93/>50,000 Direct/Indirect 50/50%,	<b>Class I</b> <b>IP20</b> <b>IK08</b>	DALI / Push Dim	Suspended, Indoor 1x2m wire kit w/ceiling bracket 5-pole Winsta mini with 5x2,5mm2 through wiring	L841 x W42 x H70
 8246094678 <b>Lineal suspended 840 White</b> <b>2690lm 4000K Ra&gt;80 DALI / Push Dim</b> <b>21W LED</b> 128 lm/W SDCM:3 L80/B10>100,000, L93/>50,000 Direct/Indirect 50/50%,	<b>Class I</b> <b>IP20</b> <b>IK08</b>	DALI / Push Dim	Suspended, Indoor 1x2m wire kit w/ceiling bracket 5-pole Winsta mini with 5x2,5mm2 through wiring	L841 x W42 x H70
<b>1120</b>				
 8246094623 <b>Lineal suspended 1120 Black</b> <b>3300lm 3000K Ra&gt;80 DALI</b> <b>29W LED</b> 114 lm/W SDCM:3 L80/B10>100,000, L93/>50,000 Direct/Indirect 50/50%,	<b>Class I</b> <b>IP20</b> <b>IK08</b>	DALI	Suspended, Indoor 1x2m wire kit w/ceiling bracket 5-pole Winsta mini with 5x2,5mm2 through wiring	L1121 x W42 x H70

Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>8246094636  <b>Lineal suspended 1120 Black</b>  <b>3470lm 4000K Ra&gt;80 DALI / Push Dim</b>  <b>29W LED</b>                      120 lm/W SDCM:3                      L80/B10&gt;100,000, L93/&gt;50,000                      Direct/Indirect 50/50%,</p>	<p><b>Class I</b>  <b>IP20</b>  <b>IK08</b></p>	<p>DALI / Push Dim</p>	<p>Suspended, Indoor                      1x2m wire kit w/ceiling bracket                      5-pole Winsta mini with 5x2,5mm2 through wiring</p>	<p>L1121 x W42 x H70</p>
 <p>8246094681  <b>Lineal suspended 1120 White</b>  <b>3590lm 3000K Ra&gt;80 DALI / Push Dim</b>  <b>29W LED</b>                      124 lm/W SDCM:3                      L80/B10&gt;100,000, L93/&gt;50,000                      Direct/Indirect 50/50%,</p>	<p><b>Class I</b>  <b>IP20</b>  <b>IK08</b></p>	<p>DALI / Push Dim</p>	<p>Suspended, Indoor                      1x2m wire kit w/ceiling bracket                      5-pole Winsta mini with 5x2,5mm2 through wiring</p>	<p>L1121 x W42 x H70</p>
 <p>8246094694  <b>Lineal suspended 1120 White</b>  <b>3830lm 4000K Ra&gt;80 DALI / Push Dim</b>  <b>29W LED</b>                      132 lm/W SDCM:3                      L80/B10&gt;100,000, L93/&gt;50,000                      Direct/Indirect 50/50%,</p>	<p><b>Class I</b>  <b>IP20</b>  <b>IK08</b></p>	<p>DALI / Push Dim</p>	<p>Suspended, Indoor                      1x2m wire kit w/ceiling bracket                      5-pole Winsta mini with 5x2,5mm2 through wiring</p>	<p>L1121 x W42 x H70</p>
 <p>8246095952  <b>Lineal 1120 White Blind profile</b>  <b>DALI / Push Dim</b></p>		<p>DALI / Push Dim</p>	<p>Surface, Indoor                      5-pole Winsta mini with 5x2,5mm2 through wiring</p>	<p>L1121 x W42 x H70</p>
 <p>8246095965  <b>Lineal 1120 Black Blind profile</b>  <b>DALI / Push Dim</b></p>		<p>DALI / Push Dim</p>	<p>Surface, Indoor                      5-pole Winsta mini with 5x2,5mm2 through wiring</p>	<p>L1121 x W42 x H70</p>
<b>1400</b>				
 <p>8246094649  <b>Lineal suspended 1400 Black</b>  <b>4280lm 3000K Ra&gt;80 DALI / Push Dim</b>  <b>37W LED</b>                      116 lm/W SDCM:3                      L80/B10&gt;100,000, L93/&gt;50,000                      Direct/Indirect 50/50%,</p>	<p><b>Class I</b>  <b>IP20</b>  <b>IK08</b></p>	<p>DALI / Push Dim</p>	<p>Suspended, Indoor                      1x2m wire kit w/ceiling bracket                      5-pole Winsta mini with 5x2,5mm2 through wiring</p>	<p>L1401 x W42 x H70</p>

Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>8246094652  <b>Lineal suspended 1400 Black</b>  <b>4500lm 4000K Ra&gt;80 DALI / Push</b>  <b>Dim</b>  <b>37W LED</b>                      122 lm/W SDCM:3                      L80/B10&gt;100,000, L93/&gt;50,000                      Direct/Indirect 50/50%,</p>	<p><b>Class I</b>  <b>IP20</b>  <b>IK08</b></p>	<p>DALI / Push Dim</p>	<p>Suspended, Indoor                      1x2m wire kit w/ceiling bracket                      5-pole Winsta mini with 5x2,5mm2                      through wiring</p>	<p>L1401 x W42 x H70</p>
 <p>8246094704  <b>Lineal suspended 1400 White</b>  <b>4640lm 3000K Ra&gt;80 DALI / Push</b>  <b>Dim</b>  <b>37W LED</b>                      125 lm/W SDCM:3                      L80/B10&gt;100,000, L93/&gt;50,000                      Direct/Indirect 50/50%,</p>	<p><b>Class I</b>  <b>IP20</b>  <b>IK08</b></p>	<p>DALI / Push Dim</p>	<p>Suspended, Indoor                      1x2m wire kit w/ceiling bracket                      5-pole Winsta mini with 5x2,5mm2                      through wiring</p>	<p>L1401 x W42 x H70</p>
 <p>8246094717  <b>Lineal suspended 1400 White</b>  <b>4960lm 4000K Ra&gt;80 DALI / Push</b>  <b>Dim</b>  <b>37W LED</b>                      134 lm/W SDCM:3                      L80/B10&gt;100,000, L93/&gt;50,000                      Direct/Indirect 50/50%,</p>	<p><b>Class I</b>  <b>IP20</b>  <b>IK08</b></p>	<p>DALI / Push Dim</p>	<p>Suspended, Indoor                      1x2m wire kit w/ceiling bracket                      5-pole Winsta mini with 5x2,5mm2                      through wiring</p>	<p>L1401 x W42 x H70</p>
 <p>8246094856 <span style="color: orange;">•</span>  <b>Lineal suspended 1400 White</b>  <b>4960lm 4000K Ra&gt;80 DALI</b>  <b>Emergency 3H</b>  <b>37W LED</b>                      134 lm/W SDCM:3                      L80/B10&gt;100,000, L93/&gt;50,000                      Direct/Indirect 50/50%,</p>	<p><b>Class I</b>  <b>IP20</b></p>	<p>DALI Emergency 3H</p>	<p>Suspended, Indoor                      1x2m wire kit w/ceiling bracket                      5-pole Winsta mini with 5x2,5mm2                      through wiring</p>	<p>L1401 x W42 x H70</p>
 <p>8246094859 <span style="color: orange;">•</span>  <b>Lineal suspended 1400 Black</b>  <b>4500lm 4000K Ra&gt;80 DALI</b>  <b>Emergency 3H</b>  <b>37W LED</b>                      122 lm/W SDCM:3                      L80/B10&gt;100,000, L93/&gt;50,000                      Direct/Indirect 50/50%,</p>	<p><b>Class I</b>  <b>IP20</b></p>	<p>DALI Emergency 3H</p>	<p>Suspended, Indoor                      1x2m wire kit w/ceiling bracket                      5-pole Winsta mini with 5x2,5mm2                      through wiring</p>	<p>L1401 x W42 x H70</p>

Article	Protection	Control gear	Mounting/Connection	Dimensions
 8249044968 <b>Lineal 2800 Front</b>			Indoor	L2800 x W38 x H4
<b>5600</b>				
 8249044971 <b>Lineal 5600 Front</b>			Indoor	L5600 x W38 x H4
<b>8400</b>				
 8249044984 <b>Lineal 8400 Front</b>			Indoor	L8400 x W38 x H4
<b>Corner</b>				
 8246094720 <b>Lineal Corner Black 1740lm 3000K</b> <b>Ra&gt;80 DALI / Push Dim</b> <b>17W LED</b> 102 lm/W SDCM:3 L80/B10>100,000, L93/>50,000 Direct,	<b>Class I</b> <b>IP20</b> <b>IK08</b>	DALI / Push Dim	Suspended, Indoor 1x2m wire kit w/ceiling bracket 5-pole Winsta mini with 5x2,5mm2 through wiring	L642 x W42 x H70 x D571
 8246094733 <b>Lineal Corner Black 1830lm 4000K</b> <b>Ra&gt;80 DALI / Push Dim</b> <b>17W LED</b> 108 lm/W SDCM:3 L80/B10>100,000, L93/>50,000 Direct,	<b>Class I</b> <b>IP20</b> <b>IK08</b>	DALI / Push Dim	Suspended, Indoor 1x2m wire kit w/ceiling bracket 5-pole Winsta mini with 5x2,5mm2 through wiring	L642 x W42 x H70 x D571
 8246094746 <b>Lineal Corner White 1870lm 3000K</b> <b>Ra&gt;80 DALI / Push Dim</b> <b>17W LED</b> 110 lm/W SDCM:3 L80/B10>100,000, L93/>50,000 Direct,	<b>Class I</b> <b>IP20</b> <b>IK08</b>	DALI / Push Dim	Suspended, Indoor 1x2m wire kit w/ceiling bracket 5-pole Winsta mini with 5x2,5mm2 through wiring	L642 x W42 x H70 x D571
 8246094759 <b>Lineal Corner White 1970lm 4000K</b> <b>Ra&gt;80 DALI / Push Dim</b> <b>17W LED</b> 116 lm/W SDCM:3 L80/B10>100,000, L93/>50,000 Direct,	<b>Class I</b> <b>IP20</b> <b>IK08</b>	DALI / Push Dim	Suspended, Indoor 1x2m wire kit w/ceiling bracket 5-pole Winsta mini with 5x2,5mm2 through wiring	L642 x W42 x H70 x D571
<b>Extension kit</b>				

Article	Protection	Control gear	Mounting/Connection	Dimensions
 8241000347 <b>Lineal Wall Extension kit White</b>				L115 x W93 x H64
 8241000348 <b>Lineal Wall Extension kit Black</b>				L115 x W93 x H64
 8241000355 <b>Lineal T-ceiling Extension kit White</b>			Indoor	L120 x W94 x H65
 8241000356 <b>Lineal T-ceiling Extension kit Black</b>			Indoor	L120 x W94 x H65
<b>Start kit</b>				
 8241000344 <b>Lineal Wall Start kit White DALI / Push Dim</b>		DALI / Push Dim	Cable 5x0,75mm <sup>2</sup> 2,5m Halogen free	L265 x W265 x H70
 8241000346 <b>Lineal Wall Start kit Black DALI / Push Dim</b>		DALI / Push Dim	Cable 5x0,75mm <sup>2</sup> 2,5m Halogen free	L265 x W265 x H70
 8241000353 <b>Lineal T-ceiling Start kit White</b>			Indoor Cable 2,5m 5x0,75 mm <sup>2</sup>	L285 x W240 x H28
 8241000354 <b>Lineal T-ceiling Start kit Black</b>			Indoor Cable 2,5m 5x0,75 mm <sup>2</sup>	L285 x W240 x H28
 8249044942 <b>Lineal Start kit Black DALI / Push Dim</b>		DALI / Push Dim	Indoor Wire Cable 5x0,75mm <sup>2</sup> 2,5m Halogen free	L140 x W140 x H55
 8249044955 <b>Lineal Start kit White DALI / Push Dim</b>		DALI / Push Dim	Indoor Wire Cable 5x0,75mm <sup>2</sup> 2,5m Halogen free	L140 x W140 x H55
<b>Others</b>				
 8249045116 <b>Lineal Wire kit 1 x 2m</b>		DALI / Push Dim	Indoor	
<b>Accessories</b>				

Article	Protection	Control gear	Mounting/Connection	Dimensions
 212198 <b>Black T-carrier ceiling bracket Aluminium</b>				L30 x W20 x H5
 212255 <b>T-profil White Suspension Rail 600mm</b>				L596 x W35 x H17
 8249045077 <b>Lineal 2240 White Blind profile Front</b>				L2240 x W38 x H4
 8249045080 <b>Lineal 2240 Black Blind profile Front</b>				L2240 x W38 x H4

• = This article is produced by order, with an expected delivery time of 3-4 weeks.