








Round surface-mounted luminaire, wholly uniform light with attractive design, made of powder-coated steel, simple to mount by removing the back plate, which can be screwed on to all known ceiling outlets/ electrical boxes, clips with option of additional looping, connectors between lamp and mounting plate, dimmable driver Phase cut-off/DALI and sensor options. Both visible and hidden cabling possible.





## Product- and environment images



Article	Protection	Control gear	Mounting/Connection	Dimensions
<b>Black</b>				
 <p>214000  <b>Circulus Black 1360lm 2700K Ra&gt;80</b>  <b>Trailing edge dimming</b>  <b>19W LED</b>            72 lm/W SDCM:3            L80/B10&gt;50,000, L70/B50&gt;100,000            Beam: 110°, Direct, Opal</p>	<p><b>Class I</b>  <b>IP21</b></p>	<p>Trailing edge            dimming</p>	<p>Surface, Indoor            Screwless terminal block</p>	<p>Ø360 x H45</p>
 <p>214001  <b>Circulus Black 1345lm 3000K Ra&gt;80</b>  <b>Trailing edge dimming</b>  <b>19W LED</b>            71 lm/W SDCM:3            L80/B10&gt;50,000, L70/B50&gt;100,000            Beam: 110°, Direct, Opal</p>	<p><b>Class I</b>  <b>IP21</b></p>	<p>Trailing edge            dimming</p>	<p>Surface, Indoor            Screwless terminal block</p>	<p>Ø360 x H45</p>
<b>Brushed steel</b>				
 <p>297000  <b>Circulus Brushed steel 1360lm</b>  <b>2700K Ra&gt;80 Trailing edge</b>  <b>dimming</b>  <b>19W LED</b>            72 lm/W SDCM:3            L80/B10&gt;50,000, L70/B50&gt;100,000            Beam: 110°, Direct, Opal</p>	<p><b>Class I</b>  <b>IP21</b></p>	<p>Trailing edge            dimming</p>	<p>Surface, Indoor            Screwless terminal block</p>	<p>Ø360 x H45</p>
 <p>297001  <b>Circulus Brushed steel 1530lm</b>  <b>3000K Ra&gt;80 Trailing edge</b>  <b>dimming</b>  <b>15W LED</b>            102 lm/W SDCM:3            L80/B10&gt;50,000, L70/B50&gt;100,000            Beam: 110°, Direct, Opal</p>	<p><b>Class I</b>  <b>IP21</b></p>	<p>Trailing edge            dimming</p>	<p>Surface, Indoor            Screwless terminal block</p>	<p>Ø360 x H45</p>
 <p>297002  <b>Circulus Brushed steel 1530lm</b>  <b>3000K Ra&gt;80 DALI / Push Dim</b>  <b>15W LED</b>            102 lm/W SDCM:3            L70/B50&gt;50,000            Beam: 110°, Direct, Opal</p>	<p><b>Class I</b>  <b>IP21</b></p>	<p>DALI / Push Dim</p>	<p>Surface, Indoor            Screwless terminal block</p>	<p>Ø360 x H45</p>
<b>White</b>				

# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>212000  <b>Circulus White 1360lm 2700K</b>  <b>Ra&gt;80 Trailing edge dimming</b>  <b>19W LED</b>            72 lm/W SDCM:3            L80/B10&gt;50,000, L70/B50&gt;100,000            Beam: 110°, Direct, Opal</p>	<b>Class I</b> <b>IP21</b>	Trailing edge dimming	Surface, Indoor Screwless terminal block	Ø360 x H45
 <p>212001  <b>Circulus White 1530lm 3000K</b>  <b>Ra&gt;80 Trailing edge dimming</b>  <b>15W LED</b>            102 lm/W SDCM:3            L80/B10&gt;50,000, L70/B50&gt;100,000            Beam: 110°, Direct, Opal</p>	<b>Class I</b> <b>IP21</b>	Trailing edge dimming	Surface, Indoor Screwless terminal block	Ø360 x H45
 <p>212002  <b>Circulus White 1345lm 3000K</b>  <b>Ra&gt;80 DALI / Push Dim</b>  <b>19W LED</b>            71 lm/W SDCM:3            L80/B10&gt;50,000, L70/B50&gt;100,000            Beam: 110°, Direct, Opal</p>	<b>Class I</b> <b>IP21</b>	DALI / Push Dim	Surface, Indoor Screwless terminal block	Ø360 x H45
 <p>212003  <b>Circulus White 1360lm 2700K</b>  <b>Ra&gt;80 Sensor</b>  <b>19W LED</b>            72 lm/W SDCM:3            L80/B10&gt;50,000, L70/B50&gt;100,000            Beam: 110°, Direct, Opal</p>	<b>Class I</b> <b>IP21</b>	Sensor	Surface, Indoor Screwless terminal block	Ø360 x H45
 <p>212004  <b>Circulus White 1530lm 3000K</b>  <b>Ra&gt;80 Sensor</b>  <b>15W LED</b>            102 lm/W SDCM:3            L70/B50&gt;50,000            Beam: 110°, Direct, Opal</p>	<b>Class I</b> <b>IP21</b>	Sensor	Surface, Indoor Screwless terminal block	Ø360 x H45