

Rax Eco 150












Rax Eco 150 is a super flexible and cost-effective downlight for general lighting in public buildings, offices, corridors etc. It has integrated switches for 3000K/4000K and for 2 lumen levels, means 4 combinations in one product. Matt white reflector providing high efficiency and low glare with UGR

Rax Eco 150



Product- and environment images



| Article | Protection | Control gear | Mounting/Connection | Dimensions |
|--|---|---|---|--------------------------|
| 3000/4000K | | | | |
|  <p>212568 Rax ECO 150 White 3000/4000K Ra>80 Trailing edge dimming LED 110/116/105/112lm/W SDCM:3 L80/B20>50,000 Beam: 89°, Direct, Reflector</p> | <p>Class II IP20</p> | <p>Trailing edge dimming</p> | <p>Indoor 3 pol Linect / screwless terminal block</p> | <p>Ø166 x H83</p> |
|  <p>212586 Rax ECO 150 White 3000/4000K Ra>80 DALI LED 1113/121/109/118lm/W SDCM:3 L80/B20>50,000 Beam: 90°, Direct, Reflector</p> | <p>Class II IP20</p> | <p>DALI</p> | <p>5 pol Linect / screwless terminal block</p> | <p>Ø166 x H83</p> |
| Others | | | | |
|  <p>820489 Sensor Dim Box White 200VA 200VA</p> | <p>IP20</p> | | <p>Indoor Screwless terminal block</p> | <p>L220 x W75 x H34</p> |
| Accessories | | | | |
|  <p>212617 Rax 150 Black Rehabring Ø155-200mm Sheet steel</p> | | | | <p>Ø220 x H16</p> |
|  <p>212620 Rax 150 White Glass clear IP44</p> | | | | <p>Ø168 x H12</p> |
|  <p>212621 Rax 150 Black Glass clear IP44</p> | | | | <p>Ø168 x H12</p> |
|  <p>212622 Rax 150 White Glass frosted IP44</p> | | | | <p>Ø168 x H12</p> |
|  <p>212623 Rax 150 Black Glass frosted IP44</p> | | | | <p>Ø168 x H12</p> |
|  <p>8249042216 Rax 150 Mounting plate Sheet steel</p> | | | | <p>L585 x W260 x H15</p> |

Article codes



| Article | Protection | Control gear | Mounting/Connection | Dimensions |
|---|------------|--------------|---------------------|------------------|
|  8249044683 Rax 150 White Rehabling Ø155-200mm Sheet steel | | | | Ø220 x H16 |
|  900109 Reliefplate Weight distribution panel Plastic | | | | L400 x W400 x H1 |