

Bell









Ceiling lamp with deep-mounted light source that provides a comfortable light without glare. Supplied with a ceiling rose. Can also be fitted in adapters for Zip 230V rails and ShopLine 3-phase rails. Bell comes in three sizes and three different color combinations: Black/White, White/White and Black/Gold.







Product- and environment images



Article codes











Article	Protection	Control gear	Mounting/Connection	Dimensions
Mini				
 <p>312361 Bell Black/White Mini 250lm 2700K Ra>90 Trailing edge dimming 5W LED 50 lm/W SDCM:3 L70/B50>50,000 Beam: 100°, Direct/Indirect, Opal</p>	<p>Class II IP20</p>	<p>Trailing edge dimming</p>	<p>Surface, Indoor Cable 3m Screwless terminal block</p>	<p>Ø160 x H205</p>
 <p>312362 Bell Black/Gold Mini 240lm 2700K Ra>90 Trailing edge dimming 5W LED 48 lm/W SDCM:3 L70/B50>50,000 Beam: 137°, Direct/Indirect, Opal</p>	<p>Class II IP20</p>	<p>Trailing edge dimming</p>	<p>Surface, Indoor Cable 3m Screwless terminal block</p>	<p>Ø160 x H205</p>
 <p>312369 Bell White/Gold Mini 240lm 2700K Ra>90 Trailing edge dimming 5W LED 48 lm/W SDCM:3 L70/B50>50,000 Direct/Indirect, Opal</p>	<p>Class II IP20</p>	<p>Trailing edge dimming</p>	<p>Surface, Indoor Cable 3m Screwless terminal block</p>	<p>Ø160 x H205</p>
Midi				
 <p>312364 Bell Black/White Midi 590lm 2700K Ra>90 Trailing edge dimming 10W LED 59 lm/W SDCM:3 L70/B50>50,000 Beam: 106°, Direct/Indirect, Opal</p>	<p>Class II IP20</p>	<p>Trailing edge dimming</p>	<p>Surface, Indoor Cable 3m Screwless terminal block</p>	<p>Ø230 x H261</p>
 <p>312365 Bell Black/Gold Midi 560lm 2700K Ra>90 Trailing edge dimming 10W LED 56 lm/W SDCM:3 L70/B50>50,000 Beam: 127°, Direct/Indirect, Opal</p>	<p>Class II IP20</p>	<p>Trailing edge dimming</p>	<p>Surface, Indoor Cable 3m Screwless terminal block</p>	<p>Ø230 x H261</p>
 <p>312370 Bell White/Gold Midi 560lm 2700K Ra>90 Trailing edge dimming 10W LED 56 lm/W SDCM:3 L70/B50>50,000 Direct/Indirect, Opal</p>	<p>Class II IP20</p>	<p>Trailing edge dimming</p>	<p>Surface, Indoor Cable 3m Screwless terminal block</p>	<p>Ø230 x H261</p>

Maxi					
	312366 Bell White/White Maxi 840lm 2700K Ra>90 Trailing edge dimming 15W LED 56 lm/W SDCM:3 L70/B50>50,000 Beam: 104°, Direct/Indirect, Opal	Class II IP20	Trailing edge dimming	Surface, Indoor Cable 3m Screwless terminal block	Ø300 x H317
	312367 Bell Black/White Maxi 840lm 2700K Ra>90 Trailing edge dimming 15W LED 56 lm/W SDCM:3 L70/B50>50,000 Beam: 104°, Direct/Indirect, Opal	Class II IP20	Trailing edge dimming	Surface, Indoor Cable 3m Screwless terminal block	Ø300 x H317
	312368 Bell Black/Gold Maxi 820lm 2700K Ra>90 Trailing edge dimming 15W LED 55 lm/W SDCM:3 L70/B50>50,000 Beam: 130°, Direct/Indirect, Opal	Class II IP20	Trailing edge dimming	Surface, Indoor Cable 3m Screwless terminal block	Ø300 x H317
	312371 Bell White/Gold Maxi 820lm 2700K Ra>90 Trailing edge dimming 15W LED 55 lm/W SDCM:3 L70/B50>50,000 Direct/Indirect, Opal	Class II IP20	Trailing edge dimming	Surface, Indoor Cable 3m Screwless terminal block	Ø300 x H317
DimToWarm					
	830913 E27 LED DimToWarm 806lm 2000-2800K Ra>80 10W 81 lm/W SDCM:6 L70/B50>50,000 Beam: 190°, Direct,		Trailing edge dimming		Ø60 x L110
	830917 E27 LED White DimToWarm 1200lm 2000-2800K Ra>80 15W 80 lm/W SDCM:6 L70/B50>50,000 Beam: 190°, Direct,		Trailing edge dimming		Ø95 x L135







Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>830922 E27 LED White DimToWarm 350lm 2000-2800K Ra>80 5W 70 lm/W SDCM:6 L70/B50>50,000 Beam: 190°, Direct,</p>		Trailing edge dimming		Ø45 x L79
Adapter - Pendant				
 <p>3046 Zip 230V White Adapter - Pendant</p>	Class II IP20		Surface, Indoor cable max Ø8mm	L84 x W23 x H90
 <p>3107 Zip 230V Black Adapter - Pendant</p>	Class II IP20		Surface, Indoor cable max Ø8mm	L84 x W23 x H90
Others				
 <p>830911 E27 806lm 2700K Ra>90 10W 81 lm/W SDCM:6 L70/B50>50,000 Beam: 190°, Direct,</p>		Trailing edge dimming		Ø60 x L110
 <p>830916 E27 LED White 1200lm 2700K Ra>90 15W 80 lm/W SDCM:3 L70/B50>50,000 Beam: 190°, Direct,</p>		Trailing edge dimming		Ø95 x L136
 <p>830918 E27 LED White 1200lm 3000K Ra>90 15W 80 lm/W SDCM:3 L70/B50>50,000 Beam: 190°, Direct,</p>		Trailing edge dimming		Ø95 x L136
Accessories				
 <p>3108 Shopline White Pendant Adapter</p>				L93 x W32 x H62
 <p>3109 Shopline Black Pendant Adapter</p>				L93 x W32 x H62

Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 314331 Black Round Ceiling Box for Pendant				Ø102 x L102 x W102 x H25
 314332 White Round Ceiling Box for Pendant				Ø102 x L102 x W102 x H25
 314333 White Recessed Ceiling Box for Pendant				Ø94 x H51
 314334 Black Recessed Ceiling Box for Pendant				Ø94 x H51
 3163 Black Ceiling Box for Pendant				Ø114 x L135 x W114
 3164 White Ceiling Box for Pendant				Ø114 x L135 x W114