

# Inspire Prism



Inspire Prism has a slim, modern design with powder-coated white or black outer surface. Direct light with prismatic, glare-free optics made of PMMA, combined with indirect light with a wide beam angle, gives an efficient light perfectly suited for offices and above desks. 2,5m cable and wireset for ceiling/T-profile fixing is included. Different control options are available; phase cut, pull-dim, Dali or SG Connect. If you want to position several luminaires in a row, the luminaires can easily be connected together with the supplied coupling piece or the flexible corner (accessory).

# Inspire Prism



## Product- and environment images



# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
<b>Black, 1200</b>				
 <p>212492  <b>Inspire 1200 Black prism 3510lm</b>  <b>3000K Ra&gt;80 Dim 1x pull switch</b>  <b>29W LED</b>            121 lm/W SDCM:3            L90/B10&gt;100,000, L96&gt;50,000            Direct/Indirect, Prism Optic</p>	<p><b>Class I</b>  <b>IP20</b></p>	<p>Dim 1x pull switch</p>	<p>Suspended, Indoor            2x2m wire kit</p>	<p>L1240 x W38 x H67</p>
 <p>212493  <b>Inspire 1200 Black prism 3510lm</b>  <b>3000K Ra&gt;80 DALI</b>  <b>29W LED</b>            121 lm/W SDCM:3            L90/B10&gt;100,000, L96&gt;50,000            Direct/Indirect, Prism Optic</p>	<p><b>Class I</b>  <b>IP20</b></p>	<p>DALI</p>	<p>Suspended, Indoor            2x2m wire kit</p>	<p>L1240 x W38 x H67</p>
 <p>212496  <b>Inspire 1200 Black prism 3620lm</b>  <b>4000K Ra&gt;80 Dim 1x pull switch</b>  <b>29W LED</b>            125 lm/W SDCM:3            L90/B10&gt;100,000, L96&gt;50,000            Direct/Indirect, Prism Optic</p>	<p><b>Class I</b>  <b>IP20</b></p>	<p>Dim 1x pull switch</p>	<p>Suspended, Indoor            2x2m wire kit</p>	<p>L1240 x W38 x H67</p>
 <p>212497  <b>Inspire 1200 Black prism 3620lm</b>  <b>4000K Ra&gt;80 DALI</b>  <b>29W LED</b>            125 lm/W SDCM:3            L90/B10&gt;100,000, L96&gt;50,000            Direct/Indirect, Prism Optic</p>	<p><b>Class I</b>  <b>IP20</b></p>	<p>DALI</p>	<p>Suspended, Indoor            2x2m wire kit</p>	<p>L1240 x W38 x H67</p>
 <p>212852  <b>Inspire 1200 Black prism 3510lm</b>  <b>3000K Ra&gt;80 Trailing edge</b>  <b>dimming</b>  <b>29W LED</b>            121 lm/W SDCM:3            L90/B10&gt;100,000, L96&gt;50,000            Direct/Indirect, Prism Optic</p>	<p><b>Class I</b>  <b>IP20</b></p>	<p>Trailing edge            dimming</p>	<p>Suspended, Indoor            2x2m wire kit</p>	<p>L1240 x W38 x H67</p>
 <p>212856  <b>Inspire 1200 Black prism 3620lm</b>  <b>4000K Ra&gt;80 Trailing edge</b>  <b>dimming</b>  <b>29W LED</b>            125 lm/W SDCM:3            L90/B10&gt;100,000, L96&gt;50,000            Direct/Indirect, Prism Optic</p>	<p><b>Class I</b>  <b>IP20</b></p>	<p>Trailing edge            dimming</p>	<p>Suspended, Indoor            2x2m wire kit</p>	<p>L1240 x W38 x H67</p>

## Black, 1500

	212862 <b>Inspire 1500 Black prism 4330lm</b> <b>3000K Ra&gt;80 Dim 1x pull switch</b> <b>35W LED</b> 124 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	<b>Class I</b> <b>IP20</b>	Dim 1x pull switch	Suspended, Indoor 2x2m wire kit	L1465 x W38 x H67
	212863 <b>Inspire 1500 Black prism 4330lm</b> <b>3000K Ra&gt;80 DALI</b> <b>35W LED</b> 124 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	<b>Class I</b> <b>IP20</b>	DALI	Suspended, Indoor 2x2m wire kit	L1465 x W38 x H67
	212866 <b>Inspire 1500 Black prism 4470lm</b> <b>4000K Ra&gt;80 Dim 1x pull switch</b> <b>35W LED</b> 128 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	<b>Class I</b> <b>IP20</b>	Dim 1x pull switch	Suspended, Indoor 2x2m wire kit	L1465 x W38 x H67
	212867 <b>Inspire 1500 Black prism 4470lm</b> <b>4000K Ra&gt;80 DALI</b> <b>35W LED</b> 128 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	<b>Class I</b> <b>IP20</b>	DALI	Suspended, Indoor 2x2m wire kit	L1465 x W38 x H67
	212870 <b>Inspire 1500 Black prism 4330lm</b> <b>3000K Ra&gt;80 Trailing edge</b> <b>dimming</b> <b>35W LED</b> 124 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	<b>Class I</b> <b>IP20</b>	Trailing edge dimming	Suspended, Indoor 2x2m wire kit	L1465 x W38 x H67
	212874 <b>Inspire 1500 Black prism 4470lm</b> <b>4000K Ra&gt;80 Trailing edge</b> <b>dimming</b> <b>35W LED</b> 128 lm/W SDCM:3 L90/B10>100,000, L96>50,000 Direct/Indirect, Prism Optic	<b>Class I</b> <b>IP20</b>	Trailing edge dimming	Suspended, Indoor 2x2m wire kit	L1465 x W38 x H67

## White, 1200

# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>212490  <b>Inspire 1200 White prism 4000lm</b>  <b>3000K Ra&gt;80 Dim 1x pull switch</b>  <b>29W LED</b>            138 lm/W SDCM:3            L90/B10&gt;100,000, L96&gt;50,000            Direct/Indirect, Prism Optic</p>	<b>Class I</b>  <b>IP20</b>	Dim 1x pull switch	Suspended, Indoor 2x2m wire kit	L1240 x W38 x H67
 <p>212491  <b>Inspire 1200 White prism 4000lm</b>  <b>3000K Ra&gt;80 DALI</b>  <b>29W LED</b>            138 lm/W SDCM:3            L90/B10&gt;100,000, L96&gt;50,000            Direct/Indirect, Prism Optic</p>	<b>Class I</b>  <b>IP20</b>	DALI	Suspended, Indoor 2x2m wire kit	L1240 x W38 x H67
 <p>212494  <b>Inspire 1200 White prism 4130lm</b>  <b>4000K Ra&gt;80 Dim 1x pull switch</b>  <b>29W LED</b>            142 lm/W SDCM:3            L90/B10&gt;100,000, L96&gt;50,000            Direct/Indirect, Prism Optic</p>	<b>Class I</b>  <b>IP20</b>	Dim 1x pull switch	Suspended, Indoor 2x2m wire kit	L1240 x W38 x H67
 <p>212495  <b>Inspire 1200 White prism 4130lm</b>  <b>4000K Ra&gt;80 DALI</b>  <b>29W LED</b>            142 lm/W SDCM:3            L90/B10&gt;100,000, L96&gt;50,000            Direct/Indirect, Prism Optic</p>	<b>Class I</b>  <b>IP20</b>	DALI	Suspended, Indoor 2x2m wire kit	L1240 x W38 x H67
 <p>212850  <b>Inspire 1200 White prism 4000lm</b>  <b>3000K Ra&gt;80 Trailing edge</b>  <b>dimming</b>  <b>29W LED</b>            138 lm/W SDCM:3            L90/B10&gt;100,000, L96&gt;50,000            Direct/Indirect, Prism Optic</p>	<b>Class I</b>  <b>IP20</b>	Trailing edge dimming	Suspended, Indoor 2x2m wire kit	L1240 x W38 x H67
 <p>212854  <b>Inspire 1200 White prism 4130lm</b>  <b>4000K Ra&gt;80 Trailing edge</b>  <b>dimming</b>  <b>29W LED</b>            142 lm/W SDCM:3            L90/B10&gt;100,000, L96&gt;50,000            Direct/Indirect, Prism Optic</p>	<b>Class I</b>  <b>IP20</b>	Trailing edge dimming	Suspended, Indoor 2x2m wire kit	L1240 x W38 x H67

White, 1500

# Article codes



Article	Protection	Control gear	Mounting/Connection	Dimensions
 <p>212860  <b>Inspire 1500 White prism 4800lm</b>  <b>3000K Ra&gt;80 Dim 1x pull switch</b>  <b>35W LED</b>                      137 lm/W SDCM:3                      L90/B10&gt;100,000, L96&gt;50,000                      Direct/Indirect, Prism Optic</p>	<p><b>Class I</b>  <b>IP20</b></p>	<p>Dim 1x pull switch</p>	<p>Suspended, Indoor                      2x2m wire kit</p>	<p>L1465 x W38 x H67</p>
 <p>212861  <b>Inspire 1500 White prism 4800lm</b>  <b>3000K Ra&gt;80 DALI</b>  <b>35W LED</b>                      137 lm/W SDCM:3                      L90/B10&gt;100,000, L96&gt;50,000                      Direct/Indirect, Prism Optic</p>	<p><b>Class I</b>  <b>IP20</b></p>	<p>DALI</p>	<p>Suspended, Indoor                      2x2m wire kit</p>	<p>L1465 x W38 x H67</p>
 <p>212864  <b>Inspire 1500 White prism 4960lm</b>  <b>4000K Ra&gt;80 Dim 1x pull switch</b>  <b>35W LED</b>                      142 lm/W SDCM:3                      L90/B10&gt;100,000, L96&gt;50,000                      Direct/Indirect, Prism Optic</p>	<p><b>Class I</b>  <b>IP20</b></p>	<p>Dim 1x pull switch</p>	<p>Suspended, Indoor                      2x2m wire kit</p>	<p>L1465 x W38 x H67</p>
 <p>212865  <b>Inspire 1500 White prism 4960lm</b>  <b>4000K Ra&gt;80 DALI</b>  <b>35W LED</b>                      142 lm/W SDCM:3                      L90/B10&gt;100,000, L96&gt;50,000                      Direct/Indirect, Prism Optic</p>	<p><b>Class I</b>  <b>IP20</b></p>	<p>DALI</p>	<p>Suspended, Indoor                      2x2m wire kit</p>	<p>L1465 x W38 x H67</p>
 <p>212868  <b>Inspire 1500 White prism 4800lm</b>  <b>3000K Ra&gt;80 Trailing edge dimming</b>  <b>35W LED</b>                      137 lm/W SDCM:3                      L90/B10&gt;100,000, L96&gt;50,000                      Direct/Indirect, Prism Optic</p>	<p><b>Class I</b>  <b>IP20</b></p>	<p>Trailing edge dimming</p>	<p>Suspended, Indoor                      2x2m wire kit</p>	<p>L1465 x W38 x H67</p>
 <p>212872  <b>Inspire 1500 White prism 4960lm</b>  <b>4000K Ra&gt;80 Trailing edge dimming</b>  <b>35W LED</b>                      142 lm/W SDCM:3                      L90/B10&gt;100,000, L96&gt;50,000                      Direct/Indirect, Prism Optic</p>	<p><b>Class I</b>  <b>IP20</b></p>	<p>Trailing edge dimming</p>	<p>Suspended, Indoor                      2x2m wire kit</p>	<p>L1465 x W38 x H67</p>